

Lok-it! 1000/PS

Lok-it! Power Series (PS)



Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

Product features and benefits

- Power Series (PS) lamps offer even more compact Lok-it! options with enhanced performance features
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Lamps designated as "Brilliant" offer exceptional color rendering with CRI as high as 95





Product datasheet

Technical data

General Product Information

Product number (Americas)	55022
Product name (Americas) LOKIT 1000/PS 10/CS 1/SKU	
Family brand	Lok-it!
Global order reference	Lok-it! 1000/PS


Electrical Data

Nominal wattage	1000 W
Nominal voltage	85 V
Nominal current	8 A

Photometric Data

Nominal luminous flux	85000 lm
Color temperature	6000 K
Color rendering index Ra	>80
Light center length (LCL)	56.0 mm

Physical Attributes & Dimensions



Electrode gap (cold)	5.5 mm
Lamp base	
Diameter (in)	0.827 in
Diameter	28.0 mm
Length	112.5 mm
Product weight	57.00 g

Operating Conditions

Burning position	Any

Product datasheet

Lifetime Data

Nominal lifetime	950 hr
------------------	--------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4052899382947 4008321788368 40528999651			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899382947	Lok-it! 1000/PS	Shipping carton box 1	115 mm x 82 mm x 305 mm	2.88 dm ³	206.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.